

this
Webinar is powered by
GameChange Solar

20 November 2025

10:00 am – 11:00 am | AWST, Perth

1:00 pm – 2:00 pm | AEDT, Sydney

pV magazine
webinars

Protecting Australian solar projects against extreme wind and hail risks



Bella Peacock

Editor
pv magazine



Scott Van Pelt

Chief Engineer
GameChange Solar



Jon Previtali

VP and Senior Principal Engineer
VDE Americas



Parsa Enshaei

Associate Principal
CPP Wind Engineering
Consultants

Welcome!



Do you have any questions? ? 🙋

Send them in via the Q&A tab. 👉 We aim to answer as many as we can today!

You can also let us know of any tech problems there.

We are recording this webinar today. 🎥

We'll let you know by email where to find it and the slide deck, so you can re-watch it at your convenience. 🤖💡



WIND ENGINEERING
CONSULTANTS

Protecting Australian Solar Projects: Extreme Wind Risks

20th November 2025

Parsa Enshaei

penshaei@cppwind.com

cppwind.com

Who We Are

- *Structural engineering + aerodynamics:*
 - Variety of structures:
 - Tall buildings, Stadiums, Bridges, Data centers, Landmarks and Monuments, Airports, etc.
 - Solar mounting systems
- *Offices around the world:*
 - US, Australia, Canada, Malaysia, India, UAE
- *Four wind tunnels:*
 - 2 in Colorado, 1 in Sydney, 1 in Kuala Lumpur





Figure: CPP services across different sectors



Australian Wind Map

- **Dynamic Pressure** = $q = 0.5\rho V^2$
- Higher recurrence interval = higher wind speeds
- 500yr MRI:
 - Region A = 45 m/s
 - Region D = 80 m/s * Mc
 - 87% higher wind speeds >> 3.5 times higher loads




Figure: Wind regions – Australia (AS/NZS 1170.2-2021)

Wind-Induced Risk



Services Throughout Site Development



Wind Tunnel Testing

- *Atmospheric Boundary Layer Wind Tunnel*
- **Simulates the gustiness of the wind at model scale**
 1. Fan drives the flow and turbulence is removed
 2. Desired turbulence levels and type is added back in throughout the 'fetch'
 3. Model is tested with the desired approach flow





Figure: CPP atmospheric boundary layer wind tunnel

Step 1: Pressure Tests

- *Rigid Pressure Models:*
- **Assumed Static Analysis**
 - Normal force and moment coefficients
 - Not covered in wind codes
- **Dynamic Amplification Factors**
 - Torsion and heaving modal excitation
 - Advanced dynamics
- **Pluck Test Review**
 - Natural frequencies of the system
 - Damping ratios for torsion and heaving




Figures:

Rigid Pressure Model (top)

CFD Vortex shedding off a flat plate (middle)

Pluck testing of a tracker (bottom)



Torsional Instability



Video: Tracker array experiencing torsional instability
(LinkedIn)



Figure: Aftermath of damage incurred:

Top: At the Oakley 2 site in October 2018 (pv magazine, 2020)

Bottom: South of Spain (Valentin et, al, 2022)

Step 2: Aeroelastic Testing

- *Scaled model that moves like a full-scale single-drive system in torsion*
- *Used to define the stow strategy and critical wind speed*



At low tilts: significant deflection + angular motion



At high tilts: minimal deflection + less motion

Staying Stable in High Wind Speeds

- Stability can be improved at moderate-high tilts by increasing the torsional damping ratio
- Aim: to test with sufficient damping levels to reach high target design wind speeds




Figure: Generic instability bounding curve




Figure: GameChange results for high wind regions

Step 3: Site-Specific Analysis


- Risk is always $> 0\%$, minimise it by understanding:

- Dominant storm types
- Directionality

Directional design wind speeds (at 10 m, open terrain)	N	E	S	W
$\hat{U}_{500,0.2}$ (m/s at 10 meters)				

- Return period vs failure costs
- Changes in directionality

Figure: Sample climate analysis including directionality



Key Takeaways


- *Quantify risk and optimise the system*
- *Wind tunnel testing to:*
 - Ensure the structure can withstand static loads
 - Dynamic amplification is accounted for
 - System is stable otherwise the rest doesn't matter
- *Site-specific analysis to assess risk for a particular system on a particular site*
 - Use local wind data to accurately design your next sites



WIND CLIMATE ANALYSIS



WIND TUNNEL TESTING



SCALE WIND TUNNEL MODELING



Thank You

Any questions?

CPP WIND ENGINEERING CONSULTANTS

500 Princes Highway
Unit 2
St. Peters, NSW 2044
Australia

T: +61 2 9551 2000
F: +61 2 9557 9447



cppwind.com



Protecting Australian Solar Projects Against Extreme Wind and Hail Risks

November 20, 2025

Scott Van Pelt – CTO



Agenda

1

Testing

CPP Wind Tunnel testing informs static and aeroelastic wind design including for sites with high design wind speeds

2

Design

Incorporating wind tunnel test results allows for accurate designs to resist extreme weather events

3

Install

Install costs can be dramatically reduced by using kitting, advanced delivery tracking and possibly robotic install

4

Operation

VDE's analysis supports insurability of operational assets and their studies validate the reliability of hail mitigation systems

Advanced Design

Genius Tracker™ System Architecture

Up to 2% More Power Production vs Typical Competitor Trackers

WeatherSmart™, PowerBoost™, and SmartStow™, combine to result in higher kWh Output and higher ROE

Pre-Assembled Drive System



50% Faster than typical competitor drive systems. No machines or driveline for industry's fastest install

Bearings

50 years accelerated life tested, over 100 years design life

Rugged Design Actuator

Zero maintenance
No grease needs to be added
40-year accelerated life testing
IP66 rated
-40/+65C [-40°F /149°F] rated

Preassembled SpeedClamps™ or Purlins
Enable the fastest install amongst all trackers per Eclipse-M

Rows up to 440 ft [135 m] Long
Can save on installation cost

Wireless Communication

LwMesh with up to 250 nodes per master
Encrypted wireless data system
No trenching for power or signal wires
1 minute polling*

Long Life 8ah Industrial Grade VRLA Battery


Typically, 8+ year field life
-40/+65C [-40°F /149°F] rated
No parasitic losses
Fast battery changeout
14ah SuperBattery option also available



Module Testing

Unbalanced Mechanical Loading to Match Real-World Loading Conditions


- Led the market to adopt this approach with 2021 PV Magazine Webinar
- Testing per site-specific wind load
- Tracker OEMs who average load over whole module risk failure onsite
- Capacity checked with both static and cyclical tests




Advanced Installation

Preassembled Driving Arm, Bottom Bracket & Drive System

Simpler Staging, Minimal Skus = Faster Install + Big Labor Cost Savings




Preassembled
Drive Arm System
(includes Bottom
Bracket Assembly)



Preassembled
Damper Arm




Preassembled
Damper Bottom Bracket



Preassembled
SpeedClamp



Preassembled
Purlin



Preassembled
Squeeze Splice



Bearing
Assembly


Industry's Best PDS (Production Delivery System)

Transparent Information

Single Point of Truth

All access the same data/dates

- Customer
- GCS
- Vendor/Port
- Carrier/Driver



Customer Portal

Provides Unparalleled Visibility and Access to Information Related to Your Projects

ProjectsDaily Pickup ReportNet Change Report

Export all Delivery Schedules

Show Active Projects Only

Project Name	Type	Size	Delivering	Status
	Tracker - 1P	140	05/20/2024 - 08/26/2024	In Production
	Tracker - 1P	104.3	04/09/2024 - 08/12/2024	In Production
	Tracker - 1P	104.3	02/19/2024 - 07/01/2024	Delivered - Structure
	Tracker - 1P	297.01	07/08/2024 - 02/03/2025	In Production

- ✓ BOM, BBA quantities and sequencing
- ✓ Change Orders
- ✓ Delivery Schedules
- ✓ Delivery Confirmation and POD management
- ✓ Inventory reconciliation
- ✓ Real time views linked to our internal delivery schedules
- ✓ Mobile access

Customer Portal

BOM By Area

Customer requested
installation sequence

Commodity	PCS12A5	PCS12A6	PCS11B2	PCS11A3	PCS11A2
Area Material Completion (Original Plan)	5/2/25	5/9/25	5/9/25	5/9/25	5/16/25
Area Material Completion (Live)	5/2/25	5/9/25	5/9/25	5/9/25	5/16/25
Area Material Completion (Delivery Plan)	4/30/25	5/7/25	5/7/25	5/8/25	5/13/25
Bearing -Preamble	4/7/25	4/7/25	4/7/25	4/7/25	4/7/25
Bracket	4/14/25	4/14/25	4/14/25	4/14/25	4/14/25
Drive System	4/22/25	4/22/25	4/29/25	4/29/25	4/29/25
Hardware	3/4/25	3/4/25	3/4/25	3/4/25	3/4/25
Post	3/27/25	3/27/25	3/27/25	3/27/25	4/7/25
Purlin Component	3/25/25	3/25/25	3/25/25	3/25/25	3/25/25
Speed Clamp	4/22/25	4/23/25	4/29/25	4/29/25	4/30/25
Splice	4/21/25	4/28/25	4/28/25	5/5/25	5/5/25
Standard Component	3/4/25	3/4/25	3/19/25	3/19/25	3/19/25
Tube	4/30/25	5/7/25	5/7/25	5/8/25	5/13/25
Electronics	6/9/25	6/9/25	6/9/25	6/9/25	6/16/25

Original Plan: Original area completion dates stipulated in the contract

Live: Latest mutually agreed upon area completion date

Delivery Plan: Date each area will be completed based on real-time Delivery Schedule data

Each commodity type can be expanded to show total required Construction, Spares and already delivered quantities and material required for each project area

	Construction	Spares	Delivered	PCS12A5	PCS12A6	PCS11B2	PCS11A3	PCS11A2
Speed Clamp				4/22/25	4/23/25	4/29/25	4/29/25	4/30/25
GC318-E-35-G180 End Clamp Insert, G180	12,316	124	12,440	556	552	556	556	556
GC4318DXH-FS6-470mm-.046/.046/.068-G90-P Preassembled SpeedClamp Dual Tabs - Heavy, 470mm, G90	154,437	155	105,600	7,272	6,912	7,272 4/29/25	6,948 4/29/25	6,948 4/30/25
GC4318DXH-FS6-870mm-.046/.053/.068L-G90-P Preassembled SpeedClamp Dual Tabs - Heavy, 870mm, G90	49,697	50	36,000	2,018	2,328	2,018	2,342	2,342 4/29/25

Visual indicators will give the user detailed information on the status of material deliveries for each areas required quantity and completion date

- Complete: Highlighted green
- On-time: Lists the date that area will be complete
- Trending late: Highlighted yellow (just in time) or Highlighted red (late)

Genius Tracker 28% Faster Than Competitors

Independent Time Study by Eclipse-M



COMPARISON TO MARKET RELEVANT 1P TRACKERS

Following is a comparison of the three competitive (market relevant) 1P trackers and two cases of the Genius Tracker. Tracker to provide some visibility to the driving factors that show the Genius Tracker to be the best in class in this comparison.

At the summary level the Genius Tracker, based on the field verified update (incorporating the maximized factory pre-assembly configuration observed being installed in Dec 2023), is 28% more productive (takes 28% less labor) than the average of the three industry competitors.

	Competitor 1 1P 650W Standard Wind	Competitor 2 1P 650W Standard Wind	Competitor 3 650W Standard Wind	GameChange Standard Wind 650W	GameChange LEAN Standard Wind 650W
Main Structure	98.1	177.6	95.8	81.0	68.9
Drive System Assembly	25.5	8.7	11.7	5.6	5.6
Module Install/ Grounding	41.2	57.7	51.3	49.5	39.6
Total MH/ MW	164.8	244.0	158.7	136.1	114.1
Better than average Tracker 1, 2 and 3 (negative is better)				-28%	-40%

SpeedClamp™ Increases Install Speed

Reduces torqued connections for panelization by 67%

Drone Captures Effortless and Unparallel Install Speed for Solar Trackers Using GameChange Solar SpeedClamp™



1. Two workers carry the module to the tube.
2. Both workers align and insert the module into the SpeedClamp™ using spacers.
3. One worker drives the two nuts to attach the SpeedClamp™ onto the tube, which simultaneously attaches and grounds the module.
4. One worker then does the final torque on all modules after completion of entire row.


Total time per module averaged **28** seconds.

This means that two workers install 1,028 modules per day, or 514 per day per worker.

Robot Assisted Installation

Useful in areas with scarce labor or labor fatigue concerns

- Support can range from simple module placement, or post install all the way up to fully autonomous installation
- Robots to assist with Panel Install already being used on GameChange projects in Texas, USA.
- Working with over a dozen robotic vendors in various levels of design and compatibility testing.



THANK YOU

MERCI 谢谢 GRACIAS

ありがとう DANKE धन्यवाद

OBRIGADO GRAZIE

Hail Risk to Solar in Australia & Real-world validation of GameChange's automated HailStow service

VDE Americas

pv magazine Webinar

November 2025

Jon Previtali, VP, VDE Americas




VDE AMERICAS

VDE Americas, the leading provider of Hail Risk Intelligence for solar




- Site- and equipment-specific hail analysis
- Probable Maximum Loss (PML) and proforma/downside reports
- Hail Risk Atlas™ ArcGIS maps (CONUS)
- Co-probability of windspeed and direction with hail
- Hail monitoring and stow protocols, tests, and 3rd party validation services
- PV module Hail Resiliency Curves with RETC test lab






Hail risk to solar in Australia

Hail risk in Australia




Brook et al, 2023

Hail risk in Australia – long term trend




Changes in hail hazard across Australia: 1979–2021 in days per decade. (Raupach et al, 2023)

Solar projects in Australia



Current solar projects (Global Energy Monitor, 2025)

Solar projects & hail risk in Australia




Current solar projects (Global Energy Monitor, 2025)

Hail risk: Brook et al, 2023



Hail monitoring & alerting in Australia

Hail monitoring in Australia: Bureau of Meteorology (BOM)



Under the radar: a technician works beneath the radar's circular dish (left); looking up at Melbourne's Laverton radar (right). (BOM)

Hail alerting services in Australia




Hail alerting services in Australia

- Weatherwatch HailTracker® / SmartHail™
- Early Warning Network (EWN) SolarAWARE
(Neither service reviewed and verified by VDE)

Best practice

- Use API query, e.g., once per minute, versus email or text alerts to improve reliability.



Source: Weatherwatch

A dramatic sky with dark, heavy clouds and bright, pinkish-purple light breaking through on the right side. The foreground shows a field of dry, brownish grass with scattered green shrubs.

GameChange HailStow Performance Validation Study

GameChange HailStow Automated Hail Protection System

Case Study: Real-World Performance Validation




Study Design

■ Parameters

- **Location:** Johnson County, Arkansas
- **Period:** April 2025
- **Method:** Independent third-party evaluation

■ Data Sources

- Monitoring & Alerting Services
 - **DTN:** 18,312 alerts (2,803 triggering)
 - **XWeather:** 776 alerts (296 triggering)
 - **National Weather Service (NWS):** NEXRAD radar + ground observations
- GameChange Solar: Activation emails, tracker positions, API logs



GameChange HailStow Automated Hail Protection System

Case Study: Real-World Performance Validation



HailStow System Configuration

- 6-minute response time
- API queries every 2 minutes
- Fully automated operation

Triggering Criteria

- 5-30 miles: Hail $\geq 0.75"$ + $\geq 30\%$ probability
- < 5 miles: Hail $\geq 0.50"$ + $\geq 30\%$ probability

Validation Test:

- A. Verify DTN and X-Weather hail alerts using NWS hail records
- B. Upon triggering, confirm HailStow system automatically:
 1. Sends activation notifications
 2. Commands trackers to protective west-facing position
 3. Maintains protective positioning for one hour after the last qualifying alert

GameChange HailStow Automated Hail Protection System

Case Study: Real-World Performance Validation



Study Results

■ Response Metrics

- Emails sent same minute as alerts
- All units met 6-minute spec
- 100% activation rate
- 19,000+ alerts processed

■ System Reliability

- 100% API uptime
- Zero manual intervention
- 24/7 monitoring capability

Event	Date Time	Duration	System Activation	Nearest Hail Observation		
				Before Activation (1)	Awaiting Confirmation (2)	Confirmed HailStow (3)
1	April 2 11:28-17:30	6 hours	Successful	None	None	14.5 mi
2	April 3 07:12-09:30	2.3 hours	Successful	None	None	21.8 mi
3	April 3 13:46-20:00	6.2 hours	Successful	None	14.8 mi	4.4 mi
4	April 4 05:22-09:00	3.6 hours	Successful	14.5 mi	10.4 mi	27.6 mi
5	April 4 15:40-19:30	3.8 hours	Successful	None	None	22.9 mi
6	April 4-5 23:30-06:00	6.5 hours	Successful	None	11.4 mi	15.5 mi


(1) Period before HailStow triggering criteria are met

(2) System activated but status not yet reported (waiting for next polling period)

(3) System status confirms trackers in protective stow position

GameChange HailStow Automated Hail Protection System

Case Study: Real-World Performance Validation



[Play Animation](#)

Thank you!

Jon Previtali
VP, VDE Americas
Jon.previtali@vde.com
+1 (415) 694-0935



© VDE

VDE AMERICAS

this
Webinar is powered by
GameChange Solar

20 November 2025

10:00 am – 11:00 am | AWST, Perth

1:00 pm – 2:00 pm | AEDT, Sydney

pV magazine
webinars

Protecting Australian solar projects against extreme wind and hail risks | **Q&A**



Bella Peacock

Editor
pv magazine



Scott Van Pelt

Chief Engineer
GameChange Solar



Jon Previtali


VP and Senior Principal Engineer
VDE Americas



Parsa Enshaei

Associate Principal
CPP Wind Engineering
Consultants

The latest news | print & online



10% off
your subscription
with
Webinars10



KPMG appointed voluntary administrators of Vast Renewables

by Ev Foley



Most-
read
online!

Ampyr to relocate 270 MW Davenport BESS to decommissioned coal station

by Ev Foley



Coming up next...

Monday, 24 November 2025

8:00 pm – 9:00 pm AEDT, Sydney

10:00 am – 11:00 am CET, Berlin, Paris, Madrid

Monday, 8 December 2025

6:00 am – 7:00 am CET, Berlin, Paris, Madrid

4:00 pm – 5:00 pm AEDT, Sydney

Many more to come!

**The future of
intelligent energy
management with
SolaX XHub**

**Safety by design:
Prefabricated EBOS
for smarter, longer
lasting solar &
BESS – NEW DATE**

In the next weeks, we will continuously add further webinars with innovative partners and the latest topics.

Check out our pv magazine Webinar program at:

www.pv-magazine.com/webinars

Registration, downloads
& recordings are also be
found there.



this
webinar is powered by
GameChange Solar

pV magazine
webinars



Bella Peacock
Editor
pV magazine

**Thank you for
joining today!**